



# Duotank frames

Bag-in-Tank principle

## Framework

In order to support the beer tanks, Duotank developed a range of frames. Which can support up to three tanks standing and multiple in a hanging frame.

## Tanks as an Eye-catcher

Finish the bar with a size frame to support the purchased tanks.

## Piping design

Duotank makes it possible to fully align the piping from the tank till the bar, in every possible material and color.

## Frames

Because the tanks are build very rigid so they can support their own weight (including beer) the tanks can be stacked in a fashionable way with standing and hanging frame types.

The frames are made of stainless steel with a glass pearl blasted finish. Optionally, the frames can be painted or copper plated.

The frames are available in various variations to allow for the creation of the best possible storage option for each unique situation and are designed and welded according the European EN1090 legislation. Standing frames are available in different set-ups, to allow for the optimal use of storage space at the bar.

For more information on these different set-ups, please look at the other side of this information sheet.

### Get in touch:

Petunialaan 5,  
5582 HA, Waalre, The Netherlands

Tel. +31 (0)40 221 22 72 / Fax. +31 (0)40 221 22 36  
Email. sales@duotank.nl



# Frames



## Non-insulated tank frames

<b>Frame 1A</b>	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1272 * 550 * 795 mm	1844 * 630 * 855 mm	2350 * 790 * 1020 mm

## Insulated tank frames

	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1314 * 625 * 889 mm	1852 * 696 * 935 mm	2384 * 860 * 1090 mm



## Non-insulated tank frames

<b>Frame 2A</b>	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1272 * 550 * 1415 mm	1844 * 630 * 1589 mm	2350 * 790 * 1900 mm

## Insulated tank frames

	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1314 * 625 * 1545 mm	1852 * 696 * 1713 mm	2384 * 860 * 2033 mm



## Non-insulated tank frames

<b>Frame 3A</b>	2,5 HL	5 HL	10 HL
Dimensions L*W*H	-	1844 * 1260 * 1399 mm	2350 * 1680 * 1660 mm

## Insulated tank frames

	2,5 HL	5 HL	10 HL
Dimensions L*W*H	-	1852 * 1392 * 1538 mm	2384 * 1720 * 1850 mm



## Non-insulated tank frames

<b>Frame 3AA</b>	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1272 * 635 * 1890 mm	1844 * 715 * 2240 mm	2350 * 880 * 2730 mm

## Insulated tank frames

	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1314 * 710 * 2155 mm	1852 * 785 * 2445 mm	2384 * 1720 * 3012 mm



## Non-insulated tank frames

<b>Hanging Frame</b>	2,5 HL	5 HL	10 HL
Dimensions L*W*H	-	-	-

## Insulated tank frames

	2,5 HL	5 HL	10 HL
Dimensions L*W*H	1314 * 714 * 711 mm	1852 * 785 * 789 mm	2384 * 946 * 946 mm